

FLOS

03.8940.40BDA White/White

Light Shadow Adjustable No Trim Dali Version 12 Spots Optic Spot UPGRADE

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|------------------|---------------------|
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| LED type | Power LED |
| Lamp category | LED |
| Number of heads | 1 |
| Power (W) | 32.4 |
| Source flux (lm) | 3240 |
| System flux (lm) | 2724 |

Physical

| | |
|--------------------------|-------------|
| Colour | White/White |
| Trim | No |
| Orientation | Adjustable |
| Longitudinal tilting (°) | 30 |
| Recessed depth (mm) | 75 |
| Length (mm) | 429 |
| Net weight (kg) | 0.66 |
| IP internal | 20 |



Drawing Thumbnail

Download

- [Mounting instructions](#) PDF
- [Mounting instructions](#) PDF

Photometric Files

- [LDT / IES](#) ZIP

Technical Drawings


- [2D](#) ZIP
- [3D](#) ZIP

Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Schematic light drawing



Photometric

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| Beam angle C0-180 (°) | 10 |
| Beam angle C90-270 (°) | 10 |

Electrical

| | |
|---------------------|---------------------------------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220 |
| Forward voltage (V) | 34.8 |
| LED current (mA) | 900 |
| Driver | Remote included |
| Dimmable | Yes |
| Dimming type | Dimmable DALI 1 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply




REQUIRED
Frame

Installation

08.0518.00

Pre-installation No Trim Frame
12L Fix Adjustable



OPTIONAL
Accessory

Mounting

08.0059.90

Accessory for mounting of No
Trim Adjustable continuous line.