



## OCULUS DL MOVE

Indoor LED ceiling recessed light black  
DIM-TO-WARM 2000-3000K

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light (2000-3000K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.

### TECHNICAL DATA

Item no.:	1004669
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250 mA/V
Vertical tilting range	30 °
Vertical tilting range	-15 °
Vertical tilting range	15 °
Height	7.3 cm
Diameter	12.0 cm
Installation diameter	10.8 cm
Installation depth	8.0 cm
Net weight	0.55 kg
Gross weight	0.589 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Ja
Dimming technology	Dim-to-Warm, trailing edge
Wattage	10.5 W
Lumen	780 lm
Beam angle	100 °



Color	white
CRI	>90
Binning	3
LXXBXX data	70/50
Service life	25000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C

### Notes

---

---

---

---

---