

FLOS

05.1412.14ACB Black/Bronze

Light Shadow Adjustable Trim Casambi Version 2 Spots Optic Medium NEW


Designed by FLOS Architectural



Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	Power LED
Lamp category	LED
Number of heads	1
Power (W)	7
Source flux (lm)	540
System flux (lm)	413

Physical

Colour	Black/Bronze
Trim	Yes
Orientation	Adjustable
Longitudinal tilting (°)	30
Recessed depth (mm)	75
Length (mm)	86
Net weight (kg)	0.25
IP internal	20

Download

[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Beam Angle: 22°

h(m)	E(lx)	D(m)
1	2901	0.38
2	725	0.76
3	322	1.14
4	181	1.52
5	116	1.91


Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50
Beam angle C0-180 (°)	21
Beam angle C90-270 (°)	21


Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable Casambi

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional

Notes

Pre-Installation frame not required.