





INFORM 40 SQ 180 PDS DOWN 94063 DIM5 W-B

30714 9435 W-B

AVAILABLE IN
BLACK-BLACK 30714 9435 B-B
WHITE-BLACK 30714 9435 W-B



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PRESENCE & DAYLIGHT SENSOR INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver EXCL.CABLE SUSPENSION

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	HO: LED cluster 27W / CRI>90 (R9: 50) / 4000K / 3987lm Or LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000 L90 > 60000
LED TECHNICS (LIGHT SOURCE)	HO: 3987lm // 27W // 148lm/W Or 2643lm // 16,3W // 162lm/W
LED TECHNICS (LUMINAIRE)	HO: 2759lm // 31W // 89lm/W Or 1829lm // 19W // 98lm/W

Options

INF40 SQ 160/180 - SUSPENSION SET
CABLE BASE R / S



INFORM 40 SQ 180 PDS DOWN 94063 DIM5 W-B

30714 9435 W-B


For detailed installation instructions, please consult the manual: [30714_XXX5_HAND.pdf](#)

INFORM 40 SQ 180 PDS DOWN 94063 DIM5 W-B

30714 9435 W-B

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W



203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W

Fixation components



30710 0010 B INF40 SQ 160/180 - SUSPENSION SET 1,6m B

30710 0010 W INF40 SQ 160/180 - SUSPENSION SET 1,6m W




30710 0030 B INF40 SQ 160/180 - SUSPENSION SET 3,0m B

30710 0030 W INF40 SQ 160/180 - SUSPENSION SET 3,0m W


INFORM 40 SQ 180 PDS DOWN 94063 DIM5 W-B

30714 9435 W-B

Other



26510 0010 PDS REMOTE CONTROL



26510 0020 PDS SENSOR PROGRAMMER

Notes: