

FLOS

09.3863.06A Chrome

Find Me 2


Designed by Jorge Herrera, 2020



Accent lighting LED module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module non-dimmable. To individually control the lights, select integrated Casambi versions.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
LED type	Power LED
Number of heads	1
Power (W)	8
Source flux (lm)	650
System flux (lm)	379
Efficacy (lm/W)	48

Physical

Colour	Chrome
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	46
Net weight (kg)	0.06
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Beam Angle: 19°

h(m)	E(lx)	D(m)
1	1709	0.34
2	427	0.67
3	190	1.01
4	107	1.34
5	68	1.68


Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	19
Beam angle C90-270 (°)	19
UGR _L	7


Electrical

Insulation class	III
Forward voltage (V)	24
LED voltage Vf (Vdc)	24.00
LED current (mA)	590
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Accessories included (honeycomb and screening crosspiece).