





SOLI - FORM 60 DOWN-UP 1 CIRCUIT 93067 DIM5 B-MMAT

27139 9325 B-MMAT

AVAILABLE IN
BLACK-BLACK 27139 9325 B-B
BLACK-GOLD MATT 27139 9325 B-MMAT
WHITE-BLACK 27139 9325 W-B
WHITE-WHITE 27139 9325 W-W



 [View on website](#)

General info

| | |
|---------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Low voltage systems Low voltage system mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.5 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | INCL.24 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC 1 CIRCUIT |

Electrical info

| | |
|---------------------|----------|
| ELECTRICAL | 48V-DC |
| CLASS | III |
| DIM TYPE | DALI |
| ENERGY CLASS | D |
| CERTIFICATES | CB, ENEC |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | DOWN: LED cluster 7W / CRI>90 (R9: 50) / 3000K / 1068lm UP: LED cluster 7W / CRI>90 (R9: 50) / 3000K / 1068lm |
| TM-30 VALUES | Rf: 92 / Rg: 100 |
| SDCM | SDCM3 |
| RISKGROUP | RG2 |
| LM80 | L80 > 60000 |
| LED TECHNICS (LIGHT SOURCE) | DOWN: 1068lm // 7W // 152lm/W UP: 1068lm // 7W // 152lm/W |
| LED TECHNICS (LUMINAIRE) | DOWN: 908lm // 8W // 113lm/W UP: 716lm // 8W // 89lm/W |

Requirements

LED POWER SUPPLY 48V-DC

SOLI - FORM 60 DOWN-UP 1 CIRCUIT 93067 DIM5 B-MMAT


27139 9325 B-MMAT

For detailed installation instructions, please consult the manual: [27139_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

6




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

15



21012 0230 LED POWER SUPPLY 48V-DC / 100W

6




21012 0240 LED POWER SUPPLY 48V-DC / 200W

12


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m





SOLI - FORM 60 DOWN-UP 1 CIRCUIT 93067 DIM5 B-MMAT

27139 9325 B-MMAT

Notes: