

FLOS

05.0915.14.NI Copper/Black/Black

Light Shadow Surface Mains Dimming Version 4 Spots Square Optic Medium NEW

Designed by FLOS Architectural, 2022



699lm - 3000K - CRI> 90

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Surface
Environments	Indoor dry location
Light Source Type	LED
LED type	Power LED
Number of heads	1
System power (W)	9
Source flux (lm)	840
System flux (lm)	699

Physical

Colour	Copper/Black/Black
Orientation	Fixed
Net weight (kg)	0.6
Package height (mm)	19
Package width (mm)	18
Package length (mm)	22
IP internal	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Beam Angle: 22°

h(m)	E(lx)	D(m)
1	4782	0.39
2	1195	0.78
3	531	1.17
4	299	1.56
5	191	1.95

Luminous flux Luminaire
699 lm (EXTREME CUT OFF)


Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B10


Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	700
Driver	Integrated
Dimmable	Yes
Dimming type	Mains Cut Dimming

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional