





## KIX S PIN 24V 93010 PGR

13529 9310 PGR

AVAILABLE IN

**ANTHRACITE (DARK GREY)** 13529 9310 N

**PINE GREEN** 13529 9310 PGR



[View on website](#)

General info	
<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Surface mounted
<b>INGRESS PROTECTION</b>	IP65
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK03
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	180° swiveling, 360° rotatable
<b>INFORMATION</b>	LENS 10° INCL.1 x CABLE H05 RN-F 2 x 1 mm <sup>2</sup> 2m EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output)

Electrical info	
<b>ELECTRICAL</b>	24V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC

Lightsource info	
<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 2W / CRI>90 (R9: 64) / 3000K / 232lm
<b>TM-30 VALUES</b>	Rf: 91 / Rg: 101
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L90B10 > 120000
<b>LED TECHNICS (LIGHT SOURCE)</b>	232lm // 2W // 116lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	165lm // 2W // 72lm/W

Requirements	
	LED POWER SUPPLY 24V-DC

Options	
	CBOX
	IP68 CONNECTION KIT
	IP68 CONNECTOR 3P

 DELTALIGHT®

**KIX S PIN 24V 93010 PGR**

13529 9310 PGR

For detailed installation instructions, please consult the manual: [13529\\_XXX0\\_HAND.pdf](#)


# KIX S PIN 24V 93010 PGR

13529 9310 PGR

## FINISH YOUR SPECIFICATION


### LED power supplies

#



**300 89 24 150** LED POWER SUPPLY 24V-DC / 150W


75



**21012 0160** LED POWER SUPPLY 24V-DC / 24W


12

### Control gear, ballast and transformers




**21032 0320** AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM)


### Waterproof connection parts



**216 12 00** CBOX



**216 12 01** IP68 CONNECTION KIT



**216 12 02** IP68 CONNECTOR 3P



**KIX S PIN 24V 93010 PGR**

13529 9310 PGR

Notes: