

# FLOS



05.2652.EQ Copper/Copper

## Light Shadow Pro Ø60 Surface Flood

Designed by FLOS Architectural, 2022




LED - LED array - 15W - 1098lm - 4000K - CRI> 90 - Beam° 32

Luminaire with low glare for surface installation. Integrated 220-240 V power supply. For dimmable versions, please refer to the recommended dimmers in the product data sheet available on the website. IP54 watertightness.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Surface
Environments	Indoor Outdoor damp location
Light Source Type	LED
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	15
System flux (lm)	1098

### Physical

Colour	Copper/Copper
Orientation	Fixed
Spot diameter (mm)	65
Length (mm)	65
Net weight (kg)	0.37
IP internal	54

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



### Ecodesign and Energy Labelling




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Schematic light drawing



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	3835	0.59
2	959	1.18
3	426	1.77
4	240	2.36
5	153	2.95

Luminous flux Luminaire  
1098 lm

### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	93
Rg gamut index	99
LED Life / Failure Ratio	L90B10_33.000_Tc=85°C
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32

### Electrical

Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Alternating current voltage (Vac)	220-240V~
Forward voltage (V)	36.1
LED current (mA)	300
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable