

FLOS

09.3603.14 Black

Find Me 3 Track

Designed by Jorge Herrera, 2022

24.5W - 2469lm - 2700K - CRI> 97 - Beam° 22

Luminaire to be installed in threephase track. Three opening angles options (Spot, Medium and Flood). DALI and Casambi dimming systems.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
LED type	LED array
Number of heads	1
Power (W)	24.5
System power (W)	25.8
Source flux (lm)	3298
System flux (lm)	2469
Efficacy (lm/W)	96

Physical

Colour	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Transversal tilting (°)	90
Spot diameter (mm)	78
Length (mm)	223
Net weight (kg)	1.18
Package height (mm)	235
Package width (mm)	265
Package length (mm)	125
Package volume (m3)	0.01
IP internal	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	97
LED Life / Failure Ratio	L90B50 > 55.000h (Tc=85°C)
Beam angle C0-180 (°)	22
Beam angle C90-270 (°)	22
Extreme cut off	Yes
UGR _L	15

Electrical


Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220
Forward voltage (V)	29
LED current (mA)	850
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Dimming interface	Not Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional