

FLOS

03.2006.14BDA Black

Bon Jour Ø 45 Dali


Designed by Philippe Starck, 2016



Recessed luminaire with LED light source. Remote 110/240V power supply included. It is necessary to anticipate a space for accessing the driver.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	Power LED
Number of heads	1
Power (W)	4.5
System power (W)	6
Source flux (lm)	605
System flux (lm)	359

Physical

Colour	Black
Trim	Yes
Recessed depth (mm)	187
Bezel diameter (mm)	45
Net weight (kg)	0.13
Package volume (m3)	0.01
IP internal	20
IP external	44

Download

Mounting instructions [↓ PDF](#)

Photometric Files


LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2468	0.34
2	617	0.67
3	274	1.01
4	154	1.34
5	99	1.68

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Rf fidelity index	91
Rg gamut index	98
LED Life / Failure Ratio	L80B20 >36000h (Tc=85°C)
Beam angle C0-180 (°)	19
Beam angle C90-270 (°)	19

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	110/240
Forward voltage (V)	11.5
LED current (mA)	400
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Accessories included (honeycomb and cross screening cylinder). Remote power supply to be installed in an accesible place.