



09.3865.14A Black

# Find Me 2

Designed by Jorge Herrera, 2020



Accent lighting LED module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module non-dimmable. To individually control the lights, select integrated Casambi versions.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

# Main specifications

Mounting	Track
Environments	Indoor dry location
LED type	Power LED
Number of heads	1
Power (W)	10.5
Source flux (lm)	650
System flux (lm)	364
Efficacy (lm/W)	35

# Physical

Colour	Black
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	46
Net weight (kg)	0.06
IP internal	20



### Download

Mounting instructions

**₩** PDF

# Photometric Files

LDT / IES

₹ ZIP

# **Technical Drawings**

2D	<b>↓</b> ZIP
3D	<b>⊥</b> ZIP
<b>a</b> Bim	<b>↓</b> ZIP




















# Schematic light drawing



Beam Angle:		32°
h(m)	E(lx)	D(m)
1	722	0.57
2	180	1.15
3	80	1.72
4	45	2.29
5	20	2 87

	пуппу	C(IX)	- 1
	1	722	0.5
	2	180	1.1
1	3	80	1.7
-	4	45	2.2

# **Ecodesign and Energy** Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

#### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32
UGR <sub>L</sub>	6

#### Electrical

Insulation class	III
Forward voltage (V)	24
LED voltage Vf (Vdc)	24.00
LED current (mA)	760
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable

# **Notes**

Accessories included (honeycomb and screening crosspiece).