

FLOS

05.7041.GL Gold

Easy Kap Ø 105 Wall-Washer

Designed by FLOS Architectural, 2019



'Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED
Lamp type	PAR16
Lamp holders	GZ10
Ilcos	No
Number of heads	1
Power (W)	MAX 3.9
System power (W)	4.2

Physical

Colour	Gold
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	125
Spot diameter (mm)	111
Net weight (kg)	0.21
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54
IP external	54



Download


[Mounting instructions](#)

[PDF](#)

Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Photometric

Lighting type	Direct
Light distribution	Asymmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	230
LED current (mA)	-9
Emergency type	No

Notes

Not suitable for lens accessories.
