


FLOS


03.7006.14 Black

Light Stripe 1200 mm

Designed by FLOS Architectural, 2017



Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|-------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | Top LED |
| Lamp category | LED |
| Ilcos | No |
| Bulb finish | Opal |
| Power (W) | 30 |
| System power (W) | 32.4 |
| Source flux (lm) | 1705 |
| System flux (lm) | 1665 |
| Efficacy (lm/W) | 51.39 |

Physical

| | |
|-----------------|-------|
| Colour | Black |
| Trim | No |
| Orientation | Fixed |
| Length (mm) | 1206 |
| Net weight (kg) | 1.36 |
| IP internal | 20 |
| IP external | 20 |

Download

[Mounting instructions](#)  PDF

Photometric Files


[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric

| | |
|--------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| LED Life / Failure Ratio | L80B50 |
| Beam angle C0-180 (°) | 108 |
| Beam angle C90-270 (°) | 105 |

Electrical

| | |
|---------------------|-----------------|
| Insulation class | III |
| Main voltage (Vac) | 24.00 |
| Forward voltage (V) | 24 |
| Driver | Remote excluded |
| Dimmable | Yes |
| Dimming type | Non Dimmable |

Notes

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.