





SOLI - FORM 60 DOWN-UP 1 CIRCUIT 93067 DIM5 W-W 27139 9325 W-W

AVAILABLE IN
BLACK-BLACK 27139 9325 B-B
BLACK-GOLD MATT 27139 9325 B-MMAT
WHITE-BLACK 27139 9325 W-B
WHITE-WHITE 27139 9325 W-W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.24 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC 1 CIRCUIT

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 7W / CRI>90 (R9: 50) / 3000K / 1068lm UP: LED cluster 7W / CRI>90 (R9: 50) / 3000K / 1068lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUPE	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 1068lm // 7W // 152lm/W UP: 1068lm // 7W // 152lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 908lm // 8W // 113lm/W UP: 716lm // 8W // 89lm/W

Requirements	
	LED POWER SUPPLY 48V-DC

SOLI - FORM 60 DOWN-UP 1 CIRCUIT 93067 DIM5 W-W


27139 9325 W-W

For detailed installation instructions, please consult the manual: [27139_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

6




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

15



21012 0230 LED POWER SUPPLY 48V-DC / 100W

6




21012 0240 LED POWER SUPPLY 48V-DC / 200W

12


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m





SOLI - FORM 60 DOWN-UP 1 CIRCUIT 93067 DIM5 W-W

27139 9325 W-W

Notes: