

FLOS

06.1634.14 Black

The Running Magnet Suspension Down Intermediate Profile


Designed by FLOS Architectural, 2015



Electromechanical profile for suspended installations. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




Main specifications

| | |
|--------------|---------------------|
| Mounting | Suspension |
| Environments | Indoor dry location |
| Iicos | No |

Physical

| | |
|-----------------|-------|
| Colour | Black |
| Trim | No |
| Length (mm) | 2500 |
| Net weight (kg) | 5.75 |
| IP internal | 20 |
| IP external | 20 |

Download

- [Mounting instructions](#)  PDF
- [Mounting instructions](#)  PDF



Electrical

Main voltage (Vac) 24.00

Notes

Covers included with the power feed profiles.

Ceiling connection (4.2 m feed cable) and suspension (4 m steel cable) accessories included in all linear feed or intermediate products.

90° corners in the same plane (symmetrical element for right and left corners) for the Surface and Down versions. Provided for connection to the driver.

The inner part of the profile is always supplied in black.

Accessories & Power Supply



 Thumbnail

OPTIONAL

Installation

08.8887.14A

Endcap. 2 unit kit

OPTIONAL

Electrical

06.1987.14

Multifunction Smart Device for
Running Magnet & Fast Track