



05.5100.14.1V Black

Find Me 0 1-10V Dimmable NEW

Designed by FLOS Architectural, 2023



LED - Power LED - 3.5W - 169lm - 2700K - CRI> 90 - Beam^o 15

LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V. Accessories included (honeycomb grid and protection bar).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

162 27 50 67

Main specifications

Mouriting	ITACK
Environments	Indoor dry location
LED type	Power LED
Lamp category	LED
Number of heads	1
Power (W)	3.5
Source flux (lm)	276
System flux (lm)	169
Efficacy (lm/W)	49

Physical

Colour	Black
Orientation	Adjustable
Rotation (°)	360
Net weight (kg)	0.06
IP internal	20

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	$\overline{\mathbf{A}}$	ZIP
3D	$\overline{\bot}$	ZIP











Ecodesign and Energy Labelling



Non-replaceable light source

https://professional.flos.com/en/global/product/find-me-0-1-10v-dimmable-05.5100.14.1v/

05.5100.14.1V

Schematic light drawing



Beam Angle:		15°
h(m)	E(lx)	D(m)
1	1925	0.26
2	481	0.52
3	214	0.77
4	120	1.03
5	77	1.29

Luminous flux luminaire 169 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	250
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable 1-10V
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)