





SPL14 - SPY 39 FOCUS 930 DIM5 FBR

27328 9305 FBR

AVAILABLE IN
BLACK 27328 9305 B
FLEMISH BRONZE 27328 9305 FBR
FLEMISH GOLD 27328 9305 FG
GOLD COLOURED 27328 9305 GC
WHITE 27328 9305 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	ADJUSTABLE BEAM 15°-45°

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
RVALUES	Rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	303lm // 10W // 31lm/W

Requirements

LED POWER SUPPLY 48V-DC


SPL14 - SPY 39 FOCUS 930 DIM5 FBR

27328 9305 FBR

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10




21012 0240 LED POWER SUPPLY 48V-DC / 200W

20


COMPATIBLE COMPOSABLES

SPLITLINE 14 profile

Available Colours



27300 0020 SPL14 - PROFILE 2m



27300 0030 SPL14 - PROFILE 3m



Notes: