



03.6820.14A Black

Light Supply Adjustable No Trim


Designed by FLOS Architectural, 2017



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	nting Ceiling recessed	
Environments	Indoor dry location	
LED type	LED array	
Lamp category	LED	
Ilcos	No	
Number of heads	1	
Power (W)	30.1	
Source flux (lm)	3164	
System flux (lm)	1639	

Physical

Colour	Black
Trim	No
Orientation	Adjustable
Rotation (°)	355
Longitudinal tilting (°)	35
Recessed depth (mm)	239
Net weight (kg)	1.01
IP internal	20
IP external	23

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	↓ ZIP
3D	⊥ ZIP
a Bim	↓ ZIP















https://professional.flos.com/en/global/product/light-supply-adjustable-no-trim-03.6820.14a/

03.6820.14A

Schematic light drawing



Beam Angle:		39°
h(m)) E(lx)	D(m)
1	4592	0.71
2	1148	1.42
3	510	2.14
4	287	2.85
5	184	3.56

Luminous flux luminaire 1639 lm (EXTREME CUT OFF)

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	39
Beam angle C90-270 (°)	39

Electrical

Insulation class	II	
Frequency (Hz)	50/60	
Main voltage (Vac)	37.60	
Driver	Remote included	
Dimmable	No	
Dimming type	Non Dimmable	
Emergency type	No	

Notes

Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.

Accessories & Power Supply



OPTIONAL Accessory

08 80/19 1/

Honeycomb. Small Cells



OPTIONAL Accessory

08.8118.68

Elliptical lens



OPTIONAL Accessory

Installation

08.8119.00

Pre-installation frame



OPTIONAL Accessory

08.8242.14

Screening crosspiece



OPTIONAL Accessory

08 8377 14

Honeycomb. Big Cells



OPTIONAL Accessory

08 8450 00

Light Supply Adjustable spare reflector. Spot



OPTIONAL Accessory

08 8451 00

Light Supply Adjustable spare reflector. Medium



OPTIONAL Accessory

08 8452 00

Light Supply Adjustable spare reflector. Flood





OPTIONAL Accessory

08 8453 40

Highly-efficient cylinder

OPTIONAL Accessory

SA 6600 1

Soft Architecture installation plate