



FRAX M 927 WALLWASH A



26011 9250 A

AVAILABLE IN

ALU GREY 26011 9250 A

FLEMISH BRONZE OUTDOOR 26011 9250 FBRX

ANTHRACITE (DARK GREY) 26011 9250 N



[View on website](#)

General info

| | |
|---|--|
| LOCATION | outdoor |
| INSTALLATION | Floor Surface mounted, Wall Surface mounted |
| INGRESS PROTECTION | IP65 |
| PROTECTION AGAINST MECHANICAL IMPACT | IK08 |
| WEIGHT (KG) | 2.4 |
| ADJUSTABILITY | 0° to 120° swiveling, 360° rotatable |
| INFORMATION | 9 x LENS SP-14° INCL.LED POWER SUPPLY 900mA-DC INCL.LINEAR WALLWASH LENS |

Electrical info

| | |
|------------------------------|--------------------|
| ELECTRICAL | 220-240V / 50-60Hz |
| CLASS | I |
| POWER SUPPLY INCLUDED | YES |
| DIM TYPE | non-dimmable |
| ENERGY CLASS | F |
| CERTIFICATES | CB |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED cluster 23,4W / CRI>90 (R9: 50) / 2700K / 2412lm |
| TM-30 VALUES | Rf: 91 / Rg: 99 |
| SDCM | SDCM3 |
| RISKGROUP | RG2 |
| LM80 | L80 > 120000 |
| LED TECHNICS (LIGHT SOURCE) | 2412lm // 23,4W // 102lm/W |
| LED TECHNICS (LUMINAIRE) | 1592lm // 27W // 59lm/W |

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX M KAP


FRAX M 927 WALLWASH A

26011 9250 A

For detailed installation instructions, please consult the manual: [26011_XX50_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Light altering devices



26070 0020 N FRAX M KAP N

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

Notes: